



EC28 D Transmitter

Ex-compliant with Display for Toxic Gases, O₂ and H₂



EC28 D Transmitter

Ex-compliant with Display for Toxic Gases, O₂ and H₂



Whenever toxic gases, hydrogen or oxygen are to be monitored and current measured values are to be displayed locally, the EC28 D transmitter combined with GfG's proven control units is the solution of choice. The ATEX-certified design means it can be used even in potentially explosive atmospheres. The hardware of the EC28 D complies with the European Functional Safety Standard DIN EN 61508-2: 2011 for many gases. The SIL levels (up to SIL3) in single-channel (1oo1) or redundant (1oo2) use are listed in the overview of gases.

Communication and Service

Communication is carried out via a 4 to 20 mA signal. The Smart Sensor technology enables fast and uncomplicated replacement of the sensor.



Display and Control Buttons

The EC28 D transmitter features a 2.2 inch LC display and three control buttons. In normal operation, the display shows the measured value or information on faults or alarms. In addition, the operating parameters (sample gas, measuring range, limit values, etc.) can be called up via the operating keys.

Remote Control RC2 (optional)

If the EC28 D has to be mounted in a difficult-to-access location, the RC2 remote control facilitates servicing and adjustments (one-man adjustment). It displays the same information that is shown on the transmitter's display.

Reliable Measurement & Minimal Operating Costs

The sensor and built-in temperature compensation ensure the highest measuring accuracy. The long sensor service life and low maintenance requirements ensure minimal operating costs.

Variants for Every Application

The basic version of the EC28 is sufficient for many applications. For specific requirements, the EC28 is also available in a wide variety of versions:

EC28	basic version for a wide range of electrochemical sensors
EC28 D	with display for showing the current measured values
EC28 DA	with display, bright LED warning lights and integrated alarm horn
EC28 DAR	with display, alarm horn and relay for additional external alarm devices
EC28 B	with Modbus interface
EC28 DB	with Modbus interface and display
EC28 DAB	with Modbus interface, display, bright LED lights and integrated alarm horn
EC28 i	intrinsically safe
EC28 Di	intrinsically safe and with display

Together with GfG's sophisticated controllers, all versions of the EC28 are the perfect choice for detecting a wide range of gases.

Overview of gases:

» Arsine (AsH ₃)	» Ethylene oxide (C ₂ H ₄ O)	» Sulphur dioxide (SO ₂)
» Bromin gas (Br ₂)	» Carbon monoxide (CO)	» Hydrogen sulphide (H ₂ S)
» Chlorine dioxide (ClO ₂)	» Ozone (O ₃)	» Nitrogen dioxide (NO ₂)
» Hydrogen cyanide (HCN)	» Phosgene (COCl ₂)	» Nitrogen monoxide (NO)
» Diborane (B ₂ H ₆)	» Phosphine (PH ₃)	» Hydrogen (H ₂)

Other gases on request

Technical Data EC28:

Measuring principle:

Electrochemical (EC)

Measuring ranges:

Depending on gas type and sensor

Gas supply:

Diffusion or gassing per calibration adapter

Expected service life of the measuring cell:

Depending on sensor

Response Time:

Depending on gas type and sensor

Temperature:

in Ex zones -20 to +50 °C

outside Ex zones -25 to +50 °C

Humidity:

5 to 90 % r. h.

Air pressure:

80 to 120 kPa

Output signal:

RS-485

Power supply:

18 to 30 V DC

Housing:

Plastic, antistatic

Protection class:

IP64

Weight:

650 g

Dimensions:

100 x 203 x 55 mm (W x H x D)

Approvals / Certifications:

Markings & Type of Protection:

Ⓜ II 2G Ex eb mb [ib] IIC T4 Gb CⓂ158
-20 °C ≤ Ta ≤ +50 °C

EU type examination certificate:

BVS 04 ATEX E 132 X

Functional Safety (SIL):

DIN EN 61508-2: 2011*

EMC Testing:

DIN EN 50270: 2015

Interference emission: Type class I

Interference immunity: Type class II

* sensor dependant

GfG Gesellschaft für Gerätebau mbH

Klönnestraße 99 | 44143 Dortmund | Germany

Phone: +49 231 56400-0 | Fax: +49 231 56400-895 | E-mail: info@gfg-mbh.com

GfGsafety.com

