

34/60/112 Litre

Aluminium Non-Refillable Cylinder



Features

- 2 year warranty (most mixtures)
- Cylinder valve compatible with all major manufacturers regulators
- Fixed flow regulators available at 0.5, 1.0, 2.5 and 3.0 LPM
- On-Demand Flow Regulator (ODFR for non-reactive, H₂S and SO₂ mixtures)
- Variflow regulator (non-reactive gases)

Contents:
34/60/1120 Litres

Service Pressure:
34bar (500psi)

Cylinder Material & Valve:
Aluminium
Connection C10 valve (5/8"-18)

Standards:
NPL, UKAS or NIST standards.
Manufactured gravimetrically to ISO 6142

Mixture Tolerances:
Minor components are certified to the following analytical tolerance
2-20ppm = +/- 10%
21-50ppm = +/- 5%
51-300ppm = +/- 2%

Warranty:

Non-reactive gases	36 months
Ethanol	24 months
H ₂ S, SO ₂ and 4 gas mixtures	12 months
NO, NH ₃ , HCN, ETO	12 months
Cl ₂ (min 5ppm)	9 months
HCl (min 5ppm)	8 months
NO ₂	6 months



GfG Gas Detection UK Ltd

Unit 8 | Griggs Business Centre | Tel.: +44 (0) 1376 561463
West Street | Coggeshall | Fax: +44 (0) 1376 561704
CO6 1NT | Essex | UK

www.gfggasdetection.co.uk
sales@gfggas.co.uk