

G999L TeamLink

Connected Safety Monitor





G999L TeamLink – The smart way to ensure Connected Safety

The one sentence that no one responsible for the safety of a colleague or a team ever wants to say is “I just lost sight of them for a moment”. With caution and technology, risks can be minimized, but accidents do still happen. All that counts in such cases is swift and targeted help.



G999L TeamLink – your Connected Safety solution

Lone work is defined as work carried out by one person alone, in isolation from other workers without close or direct supervision, even if only for a short time. If this cannot be avoided, employers must take appropriate monitoring measures.

The G999L TeamLink Connected Safety Monitor wirelessly links the gas detection devices of up to ten team members into a safety network that provides important information in real time in case of an alarm.

Functions:

- » Query the measured values of up to ten connected gas detection devices in real time
- » Continuously monitoring radio connections
- » Providing team leaders with visual and audible alarms, including information on affected persons and gas concentrations
- » Man-down Alarm and Panic Alarm
- » LED panel for a quick overview
- » On-going information of hazard situations on site to enable rescue services to protect themselves
- » Open field range up to 984 feet / 300 meters
- » Ex-approval for I M2 / II 2G

The next logical step in occupational safety: Connected Safety

The primary purpose of portable gas detection devices is to alert the user and people in the immediate vicinity of dangerous gas concentrations. However, this alone is not enough. Information about an alarm and its cause must be available to the supervising person, i.e. the team leader, supervisor or the second man of a buddy system.

This is the only way to alert other team members in case of an emergency and to initiate measures without rescuers putting themselves at risk or losing too much time with self-protection against unknown dangers.

Clearly visible and unmistakable (103 dB):



LED panel information:



Red	static	Alarm (gas, man-down, panic)
Green/Yellow	flashing	Connection interrupted
Yellow	flashing	Connection not possible
Yellow	static	Device off/Service mode
Green	static	Everything is OK

The TeamLink - a safer and more economical solution than other security concepts

Know what is happening on site

When every second counts, the situation on site must be clear at first glance. In the event of an alarm, the TeamLink shows unambiguously whether there is a dangerous situation caused by gas (**Alarm Thresholds 1 to 3**), whether the person on site is actively requesting help (**Panic Alarm**) or whether there is a medical emergency (**Man-down Alarm**).

« React as soon as risks arise. »

Be aware when additional measures need to be taken

The TeamLink not only alerts the user to acute dangers, but also indicates as soon as a gas detector can no longer be reached. A yellow display in the LED panel is the signal for the supervisor to take action. It may be enough for a worker to change their position to restore the connection, however, additional measures, such as a buddy system, may become necessary if local conditions do not allow for remote monitoring.

Exploring without endangering lives

The combination of the portable gas monitor and TeamLink is also perfect for checking gas concentrations from a safe distance and detecting hazards in time. For example, this allows, the use of remote-controlled reconnaissance vehicles to minimize potential risks for employees or rescue teams.



Connected Safety Utilizing TeamLink and G888/G999 Visual

The TeamLink is only one component in GfG's Connected Safety network. The other is the G888/G999 Visual safety software. Installed on a laptop or tablet, it quickly and conveniently connects with all team members using a USB radio dongle, offering additional security functions such as:

- » Monitoring of teams with more than 10 members
- » Pager function for short messages and answers
- » Simulated alarms for safety exercises

All the data and information that is displayed by the TeamLink is clear and concise. The TeamLink is suitable for use with both the Microtector G888 and Polytector G999. These portable gas monitors must be equipped with an appropriate radio module.

CONNECTED SAFETY



Technical Data: G999L TeamLink

Type designation:	G999L	
Purpose:	Portable Connected Safety Monitor for status and measurement data retrieval by radio from G888 and G999 series gas detectors.	
Display:	Illuminated 2 inch LC full graphic display	
Power supply:	NiMH battery module, 5.2 V, 2100 mAh	
Environmental conditions:	Temperature for storage: -13 to +131 °F / -25 to +55 °C Temperature for operation: -4 to +122 °F / -20 to +50 °C Humidity: 5% to 95% r.h. Pressure: 70 kPa to 130 kPa	
Alarms:	According to the configuration of the integrated, portable gas detectors	
Radio:	USA: 915 MHz Range approx. 984 ft / 300 m (open field)	
Housing:	Material: Shock absorbing, rubberized polycarbonate Dimensions: 2.7 x 5.4 x 1.5 in / 68 x 136 x 39 mm (W x H x D) Weight: 11 oz / 306 g Protection Class: IP67 Mounting: Crocodile clip	
Approvals / Certifications:	Labeling & Type of Protection: Ex I M2 Ex ib I Mb Ex II 2G Ex ib IIC T4 Gb -20 °C ≤ Ta ≤ +50 °C EU-Type Examination Certificate: BVS 15 ATEX E 064 X IECEx Certificate of Conformity: IECEx BVS 15.0056 X Electromagnetic Compatibility: DIN EN 50270:2015 Interference emission: Type class I Immunity to interference: Type class II	



www.gfgsafety.com/us-en

© GfG Instrumentation, Inc. 2022
All specifications on this brochure are subject to technical changes due to further development.

USA and Canada
Latin America
Germany
South Africa
Asia Pacific
Great Britain
Switzerland
France
Poland
Austria
Netherlands

info@goodforgas.com
info@goodforgas.com
info@gfg-mbh.com
info@gfg.co.za
sales@gfg-asiapac.sg
sales@gfggas.co.uk
info@gfg.ch
alainflachon@gfg-gasdetection.fr
biuro@gfg.pl
austria@gfg-mbh.com
info@gfg-gasdetection.nl



GfG Instrumentation, Inc.
1194 Oak Valley Drive, Suite 20, Ann Arbor, MI 48108 USA
Phone: (734) 769-0573 • Toll Free (USA / Canada): (800) 959-0329
Website: www.gfgsafety.com/us-en • info@goodforgas.com