



Gas Safety Solutions for the Industrial

Safety Industry

GfGsafety.com/us-en

Protection from atmospheric hazards where invisible, toxic fumes and deadly gases may be present in industrial environments



G888

- For toxic and flammable gases, as well as O₂
- Five (5) year Lead Free Oxygen (O2) sensor
- Optional RF 915 MHz radio module
- Man-down alarm and ability to monitor individual workstations



G999

- Large sensor selection, five sensor slots to measure toxic / flammable gases / vapors, VOC's and O
- Real time data, alarms, and man-down using optional radio module, monitored from a central control center
- Integrated pump technology features a dynamic flow monitoring system which displays the intake flow rate



G222E

- Dual gas detector for monitoring a wide range of toxic gases such as CO, HCN and HF
- Simple, two-button menu and large, easy-to-read display
- Average operating time of up to 9 months, depending on sensors
- Internal data logger stores the last 2,600 events



G450

- » Continuously measures up to four gas hazards (CO, H₂S,
- » 3-year warranty on all sensors
- Robust, dust proof and highly water resistant (IP67) housing
- Delivers up to 24 hours of continuous operation in either two "AA" alkaline batteries or a NiMH rechargeable battery pack



G460

- Continuously measures up to six gas hazards
- Wide range of sensors including PID for VOC's, infrared (NDIR) for CO₂ and many more!
- Top-mounted display changes color to indicate severity of the hazardous condition
- GfG AutoCal® programming makes calibration simple



Micro IV

- Simple, pocket-sized single gas detector for personal safety
- Wide range of long-lasting, interchangeable smart-sensors
- Delivers up to 3,000 hours of battery life using a single AA alkaline battery
- Large graphic display and loud, vibrating and visual alarms